

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
18 December 2003 (18.12.2003)

PCT

(10) International Publication Number  
WO 03/103745 A2

(51) International Patent Classification<sup>7</sup>: A61M

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/US03/18644

(22) International Filing Date: 11 June 2003 (11.06.2003)

(25) Filing Language: English

(84) Designated States (regional): ARIGO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language: English

(30) Priority Data:  
60/388,136 11 June 2002 (11.06.2002) US

Published:

— without international search report and to be republished upon receipt of that report

(71) Applicant and

(72) Inventor: ABOUL-HOSN, Walid [US/US]; 4625 Chicago Avenue, Fair Oaks, CA 95628 (US).

(74) Agent: SPANGLER, Jonathan; 2875 Kalmia Place, San Diego, CA 92104 (US).


(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(55) Title: EXPANDABLE BLOOD PUMP AND RELATED METHODS



WO 03/103745 A2



(57) Abstract: The present invention involves a blood pump having a blood pump and internally disposed rotor, wherein each of the pump housing and rotor are capable of being expanded from a first state of generally reduced dimension to a second state of generally increased dimension. The blood pump may be advantageously introduced into the patient (and onward to the pumping site) while in the first state and thereafter operated (automatically or manually) into the second state for use in pumping blood to augment or replace the pumping capacity of the patient's heart.